

CB COLOR LEI

ELASTIC, WATERBORNE COLOURED COATING FOR ROOFS COMPOSED OF ACRYLIC RESINS WITH INTERNAL SOFTENING

APPLICATION

CB Color Lei is used for the solar protection of roofing roofs and waterproofing of various slightly sloping and inclined building materials such as roofing, zinc, shingles, tiles, corrugated sheets in asbestos cement and fibre cement,... Waterproofing of joints around fireplaces, eaves, skylights, domes,...

PRODUCT DESCRIPTION

CB Color Lei is a viscous paste, ready for use and comes in various colours. After drying, **CB Color Lei** forms a seamless, elastic fleece that bridges cracks. The formed membrane is breathable, U.V.-resistant, resists various chemicals and contaminants, is flame-retardant and non-flammable.

CHARACTERISTICS

Form	: viscious
Specific weight	: +/- 1,5
Percentage of dry powders	: +/- 74%
Type of raw material	: modified acrylates
Solvent	: water
Watertightness	: total from 500g/m ²
Water vapour permeability	: +/- 120g/m ² 24h/500g/m ²
Stretching power	: >400%
Contraction after elongation	: 100%
Hardness	: Shore A min.45

DIRECTIONS

PREPARATION

The substrate must have the necessary load-bearing capacity, be healthy, clean, stripped of doubtful and loose layers and be sufficiently dry. Pre-treat highly absorbent, powdery and critical substrates with a dilution of *CB Latex* (see technical data sheet).

WORKING METHODE

Apply **CB Color Lei** with a roller, brush, rubber swab or airless, in case of waterproofing in at least 2 layers.

WARNING

The minimum film forming temperature of **CB Color Lei** is 10°C. Do not apply **CB Color Lei** in case of rain, threatening rain, frost or night frost. Do not use **CB Color Lei** when the film is constantly under

water. Transport and store the product frost-free. The material can be cleaned immediately after use with water or soapy water.

USAGE/DOSAGE

Flat roofs with roofing, zinc...

As protection +/- 350 g/m²

As renovation +/- 1500 g/m²

Sloping roofs with tiles, corrugated iron ...

As renovation +/- 1000 g/m²

TRANSPORT – SHELF LIFE - PACKAGING

Transport and store frost-free. Protect the product and its packaging from direct sunlight. Avoid storage at temperatures >30°C.

1 year after manufacture in the original, closed packaging.

25 kg buckets

CONSIDERATION - EPILOGUE

The information in this technical sheet is based on extensive research and experience. However, the information is provided without any guarantee - directly implied - as to its correctness. The conditions or methods of handling, storage, use of the product are beyond our control and may also be beyond our knowledge. For these and other reasons, we accept no liability for damage or nuisance of any kind, caused by the use of the product in question. The indicated characteristics and properties are average values and analyses obtained at 20 °C, deviations are tolerated. The rewrite of this sheet replaces all previous sheets.